

PIG Oil-Only Absorbent Booms

BOM405

13 cm x 3 m, Absorbs up to 90.8 L per bag, 4 booms per bag

Control oil spills on land or water with the field-proven performance of PIG Booms.



- Field-proven performance — works in all conditions to absorb oil spills on land or water
- Floats to confine and soak up spills on water; hugs ground for land-based spills
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 182kg loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant for up to 12 months; meets ANSI and MIL-spec standards for static decay
- Booms float at the surface for easy retrieval, even when saturated
- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for increased length
- Bright white colour makes booms easier to see in outdoor environments and clearly shows the saturation level
- Can be incinerated after use to reduce waste or for fuels blending
- When sea-weather condition is wind speed >5 knots & a (perpendicular) water-current speed >2 knots, this can cause oil absorbent booms to submerge, allowing oil to pass over them
- Waves higher than freeboard (above water) portion of boom will push oil over absorbent booms; optimal sea-weather condition for usage is typically Beaufort Scale #2 or less



Specifications

Absorbency Per Selling Unit	Up to 90.8 L per bag
Certification	ANSI/ESD STM11.11, MIL-STD-3010C
Colour	White
Composition	Polypropylene Sleeve & Filler; Polyester Netting; Plated Steel Rings & Clips
Exterior Diameter	13 cm
Fluids Absorbed	Oil-Based Liquids But Not Water
Length	3 m

Recycled Material	98% Pre-Consumer Recycled Polypropylene Filler
Weight	9.7 kg
Sold as	4 Booms per Bag

Documentation

[STORAGE & SHELF LIFE OF PIG ABSORBENTS & ABSORBENT SPILL KITS](#)

[TECHNICAL DATA SHEET PIG® OIL-ONLY ABSORBENTS](#)

Certifications, Approvals and Ratings

ANSI/ESD STM11.11, MIL-STD-3010C

New Pig Ltd.

Hogs Hill • Watt Place • Hamilton International Technology Park
Blantyre • Glasgow • United Kingdom • G72 0AH

+44 (0)800 919 900

New Pig B.V.

Concorde 5 • 5126 RM Gilze • The Netherlands

+31 (0)76 596 9250 (English)
+33 (0)800 90 30 22 (French)
+49 (0)800-1-827-487 (German)
+39 800 874 60 (Italian)

newpig.co.uk
pigpen@newpig.com

newpig.eu
pigpost@newpig.com



New Pig