

Drop-Ceiling Leak Diversion System

TLS367

61 cm x 122 cm

Leak diversion system replaces damaged ceiling tile for discrete channeling of liquids until you find and fix the leak.

- Remove damaged tile and replace it with a leak diversion system panel to channel away liquids
- Minimises wet floors, damaged equipment and disturbances to workers
- Captures leaks and drips and diverts them to a drain or storage tank using the included hose
- · Includes drain hose and clips to secure hose to ceiling grids
- Flow rate of 3.8-litres per minute when used with included hose
- After leak has been repair, uninstall and store for later use
- Replaces any standard 61cm x 122cm drop ceiling tile





Specifications

Additional Grommets Per Side	N/A
Colour	White
Composition	Ceiling Diverter - Polystyrene; Hose - PVC; Pipe Connector - Polypropylene; Plastic Clips - Polypropylene; Ties - Polyamide
Corner Style	N/A
Drainage Hose	Included
Flow Rate	0.76 ltr. per minute
Hanging Straps	N/A
Hose Connector	.5"
Installation Method	Frame

1 - 61cm x 61cm Drop-Ceiling Panel 1 - 7.6m L Drain Hose 6 - Ceiling Clips 9 - Tie Wraps
122 cm
Rectangle
N/A
Drop Ceilings
61 cm
3.6 kg
1 Each

Disclaimers

Not suitable for temperatures over 170°F/77°C.

New Pig Ltd. Hogs Hill • Watt Place • Hamilton International Technology Park Blantyre • Glasgow • United Kingdom • G72 0AH

+44 (0)800 919 900

New Pig B.V. Concorde 5 • 5126 RM Gilze • The Netherlands

+31 (0)76 596 9250 (English) +33 (0)800 90 30 22 (French) +49 (0)800-1-827-487 (German) +39 800 874 60 (Italian)

newpig.co.uk pigpen@newpig.com

newpig.eu pigpost@newpig.com

