











Specifications



PIG® Leak Diverter for Roofs

TLS554-GY

305 cm x 610 cm

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!

- The original Leak Diverter invented here and engineered to stop devastating roof leak damage every time, guaranteed!
- Long, rectangular shape is ideal for catching leaks or accumulated condensation along cracks, fissures or pipes
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for longterm prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long product life
- Pinched corners help funnel liquid toward centre for better drainage
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose
- Heavy D-rings and grommets resist tearing and make installation easy

Thickness	Clear - 300 micron, Colours - 400 micron
Total Grommets/D-Rings	16 Grommets and 4 D-Rings
Use With	Roofs
Width	305 cm
Weight	6.05 kg
Sold as	1 Each

Disclaimers

Not suitable for temperatures over 170°F/77°C.

Dimensions are nominal size due to pinched corners and reinforced side walls.

New Pig Ltd.

Hogs Hill • Watt Place • Hamilton International Technology Park Blantyre • Glasgow • United Kingdom • G72 0AH

+44 (0)800 919 900

New Pig B.V.

Concorde 5 • 5126 RM Gilze • The Netherlands

+31 (0)76 596 9250

+33 (0)800 90 30 22 (French) +49 (0)800-1-827-487 (German)

+39 800 874 60

(Italian)

newpig.co.uk pigpen@newpig.com

newpig.eu pigpost@newpig.com

